

## DFWK-HGX

### DFWK HYGIENX: New Multifunctional Weight Indicator for Industrial Industries with High Hygiene Requirements



The DFWK HYGIENX Weight Indicator features a robust **AISI 316 stainless steel** casing and **IP68 and IP69K** protection ratings, which ensure fast and deep sanitization with high-temperature and high-pressure water jets.

In the chemical industry, as in the pharmaceutical and food industries, it is necessary to ensure thorough cleaning and exclude any risk of chemical, physical or bacterial contamination.

Weight indicator with internal rechargeable battery. CE-M approved (OIML R-76 / EN 45501).

#### Working in cooperation with:

##### **IBEROTEC SAS** Basculas y Refrigeracion

Carrera 42 (Autopista Sur) # 54 A-71 - Bodega 115 ESPACIO SUR Itagui - - Antioquia  
Tel. 0057 4 4441223  
Ventas@iberotecsas.com

**The best solution  
for advanced industrial  
applications**

## MAIN FEATURES

- Waterproof 17-key numeric-functional keypad
- Backlit 25 mm LCD display with 6 high-contrast digits, with icons for indicating active functions
- AISI 316 stainless steel enclosure
- IP68 and IP69K certification against water, dust and high-pressure hot water jets
- Dimensions: 280x143x185 mm
- 24 bit A/D converter, 4 channels max. 200 conv./sec. Autoselect and up to 8 signal linearization points
- Max 10,000e or multi-field 3 x 3000e @ 0.3  $\mu\text{V/e}$  in CE-M approved version for legal for trade systems
- Max 1,000,000 displayable divisions for internal factory use with internal resolution up to 3,000,000 points
- Connection to max. 8 load cells with 350 Ohm input resistance or max. 16 cells with 700 Ohm input resistance
- Digital calibration and set-up from keyboard or PC with DINITOOLS
- Internal rechargeable battery with autonomy up to 60 hours
- 110-240 Vac power supply via 1.5 m cable with Shuko plug

## I/O SECTION

- Bi-directional RS232/C port configurable for connection to remote printer/labeler
- Bi-directional RS232/C (optional RS485) port configurable for PC, PLC, additional remote display or radio modem

## MAIN CERTIFICATIONS

- EU Type Examination Certificate (45501:2015)
- OIML R76
- Australian legal for trade certificate of approval (NMI S788)
- IP68 and IP69K protection rating

## FUNCTIONS AVAILABLE FROM REMOTE CONTROL

- 6-key radio frequency remote control:  
zero; tare; enable/disable function; print; shutdown.

## FUNCTIONS

- Operation modes selectable directly by the user, via dedicated key\*:
- High-resolution display x 10
- Precision weighing with temporary recalibration by sample weight (for internal factory use)
- Net/Gross
- lb/kg conversion
- Free conversion factor (for meter-counting systems, liter counters etc.)
- Weights totalization
- Formulation
- +/- control, with rapid target and threshold entry
- Percentage weighing
- Percentage dosing with programmable target
- Piece counting
- Hold
- Two-speed filling/dosing with zeroing at start (with optional DFIO).

The "alibi memory" and "setpoint" functions are available in combination with the desired mode of operation and are automatically activated when the corresponding optional board is installed; thus, for example, totalizing, saving each alibi memory weighing, and activating relay outputs are possible.

- *\*These quick menu access keys can be inhibited by configuring a dedicated password.*



[www.diniargeo.com](http://www.diniargeo.com)

“YOUR WORLDWIDE PARTNER FOR WEIGHING,”

DINI ARGEO  
FRANCE sarl  
France

DINI ARGEO  
GMBH  
Germany

DINI ARGEO  
UK Ltd  
United Kingdom

DINI ARGEO WEIGHING  
INSTRUMENTS Ltd  
China

DINI ARGEO  
OCEANIA  
Australia



**COMPANY HEADQUARTERS**

Via Della Fisica, 20  
41042 Spezzano di Fiorano - Modena - Italy  
Tel. +39.0536 843418

***IBEROTEC SAS Basculas y Refrigeracion***

Carrera 42 (Autopista Sur) # 54 A-71 - Bodega 115 ESPACIO SUR Itagui - - Antioquia

Tel. 0057 4 4441223

[Ventas@iberotecsas.com](mailto:Ventas@iberotecsas.com)

**SALES AND TECHNICAL ASSISTANCE SERVICE**